

# 55000 STRAIGHT MALE ADAPTOR "UNIVERSAL SHORT"

Материал Brass/PVC/1.0619

Налягане PN 20

Размер Ø4,0 - Ø14,0 mm

## APPLICATIONS

- Pneumatic automation
- Automotive
- Textile, Packaging
- Compressed Air Circuit
- Vacuum

## VARIANTS AND ADVANTAGES

- Quick connection and disconnection
- Full Flow and Vacuum resistant tank to special shaped seals
- 3 threads available:
  - BSPP
  - BSPT (universal short)
  - Metric
- Metal Robustness
- Wide Range
- Silicon Free



No.	Parts	Material
1	Body	Nickel-plated brass
2	Rings	Acetalic resin
3	Capsule	Nickel-plated brass Capsule
4	Clamping washer	Steel AISI 301
5	Position ring	Technopolymeric
6	Molded seal	NBR
7	Thread packing	NBR
8	Threaded base	Nickel Plated Brass
9	Seeger	Seeger
10	Seal	NBR

Specifications	
Standards Reference:	ROHS 2011/65/CE
	PED 2014/68/UE
	ISO 14743:2004
	Sillicon free
Tube diameter:	4,0 - 14,0 mm

Code	Tube	A	B	L	Ch1	Ch2	Bag
------	------	---	---	---	-----	-----	-----

## 55000 STRAIGHT MALE ADAPTOR "UNIVERSAL SHORT"

Материал Brass/PVC/1.0619

Налягане PN 20

Размер Ø4,0 - Ø14,0 mm

Code	Tube	A	B	L	Ch1	Ch2	Bag
5500000001	4	1/8	5.5	18	11	3	10
5500000013	4	1/4	7	19	14	3	10
5500000002	5	1/8	5.5	20	11	4	10
5500000003	5	1/4	7	20	14	4	10
5500000004	6	1/8	5.5	21.5	13	4	10
5500000005	6	1/4	7	21	14	4	10
5500000014	6	3/8	7.5	23	17	4	10
5500000015	6	1/2	9	23.5	21	4	10
5500000006	8	1/8	5.5	24.5	14	5	10
5500000007	8	1/4	7	22	14	6	10
5500000008	8	3/8	7.5	23	17	6	10
5500000016	8	1/2	9	23.5	21	6	10
5500000009	10	1/4	7	28	17	7	10
5500000010	10	3/8	7.5	25.5	17	8	10
5500000017	10	1/2	9	26	21	8	10
5500000011	12	1/4	7	31.5	20	7	10
5500000012	12	3/8	7.5	29.5	20	9	10
5500000018	12	1/2	9	31.5	21	10	10
5500000019	14	3/8	7.5	32.5	21	9	10
5500000020	14	1/2	9	31.5	21	10	10