

55040 STRAIGHT CONNECTOR

Материал Brass/PVC/1.0619

Налягане PN 20

Размер Ø4,0 - Ø14,0 mm

APPLICATIONS

- Pneumatic automation
- Automotive
- Textile, Packaging
- Compressed Air Circuit
- Vacuum

VARIANTS AND ADVANTAGES

- Quick connection and disconnection
- Full Flow and Vacuum resistant tank to special shaped seals
- 3 threads available:
 - BSPP
 - BSPT (universal short)
 - Metric
- Metal Robustness
- Wide Range
- Silicon Free



No.	Parts	Material
1	Body	Nickel-plated brass
2	Rings	Acetalic resin
3	Capsule	Nickel-plated brass Capsule
4	Clamping washer	Steel AISI 301
5	Position ring	Technopolymeric
6	Molded seal	NBR
7	Thread packing	NBR
8	Threaded base	Nickel Plated Brass
9	Seeger	Seeger
10	Seal	NBR

Specifications	
Standards Reference:	ROHS 2011/65/CE
	PED 2014/68/UE
	ISO 14743:2004
	Sillicon free
Tube diameter:	4,0 - 14,0 mm

Code	Tube	Tube2	L	B	Bag
------	------	-------	---	---	-----

55040 STRAIGHT CONNECTOR

Материал Brass/PVC/1.0619

Налягане PN 20

Размер Ø4,0 - Ø14,0 mm

Code	Tube	Tube2	L	B	Bag
5504000002	4	4	31	10	10
5504000003	5	5	34	12	10
5504000004	6	6	35	12.5	10
5504000009	6	4	34	12.5	10
5504000005	8	8	37	14	10
5504000015	8	4	37	14	10
5504000010	8	6	37	14	10
5504000006	10	10	45	17	10
5504000014	10	6	44	17	10
5504000011	10	8	44	17	10
5504000007	12	12	50	20	10
5504000016	12	8	50	20	10
5504000012	12	10	50	20	10
5504000008	14	14	48	21	10
5504000017	14	12	48	21	10