

55111 ORIENTING ELBOW MALE "UNIVERSAL SHORT"

Материал Brass/PVC/1.0619

Налягане PN 20

Размер Ø4,0 - Ø14,0 mm

APPLICATIONS

- Pneumatic automation
- Automotive
- Textile, Packaging
- Compressed Air Circuit
- Vacuum

VARIANTS AND ADVANTAGES

- Quick connection and disconnection
- Full Flow and Vacuum resistant tank to special shaped seals
- 3 threads available:
 - BSPP
 - BSPT (universal short)
 - Metric
- Metal Robustness
- Wide Range
- Silicon Free



No.	Parts	Material
1	Body	Nickel-plated brass
2	Rings	Acetalic resin
3	Capsule	Nickel-plated brass Capsule
4	Clamping washer	Steel AISI 301
5	Position ring	Technopolymeric
6	Molded seal	NBR
7	Thread packing	NBR
8	Threaded base	Nickel Plated Brass
9	Seeger	Seeger
10	Seal	NBR

Specifications	
Standards Reference:	ROHS 2011/65/CE
	PED 2014/68/UE
	ISO 14743:2004
	Sillicon free
Tube diameter:	4,0 - 14,0 mm

Code	Tube	A	B	L1	L2	Ch1	Ch2	D	Bag
------	------	---	---	----	----	-----	-----	---	-----

55111 ORIENTING ELBOW MALE "UNIVERSAL SHORT"

Материал Brass/PVC/1.0619

Налягане PN 20

Размер Ø4,0 - Ø14,0 mm

Code	Tube	A	B	L1	L2	Ch1	Ch2	D	Bag
5511100001	4	1/8	5.5	16.5	16.5	7	13	10	10
5511100002	4	1/4	7	16.5	18	7	15	10	10
5511100003	5	1/8	5.5	20	17,4	9	13	12	10
5511100004	6	1/8	5.5	20.5	17,4	9	13	12	10
5511100005	6	1/4	7	20.5	18,9	9	15	12	10
5511100006	6	3/8	7.5	20.5	20	9	17	12	10
5511100007	6	1/2	9	20.5	22	9	21	12	10
5511100008	8	1/8	5.5	22	18,5	10	13	14	10
5511100009	8	1/4	7	22	20	10	15	14	10
5511100010	8	3/8	7.5	22	20,5	10	17	14	10
5511100011	8	1/2	9	22	23	10	21	14	10
5511100012	10	1/4	7	26,5	21,8	13	16	17	10
5511100013	10	3/8	7.5	26,5	21,8	13	17	17	10
5511100014	10	1/2	9	26,5	24,3	13	21	17	10
5511100015	12	1/4	7	30	23,1	16	16	20	10
5511100016	12	3/8	7.5	30	23,1	16	17	20	10
5511100017	12	1/2	9	30	25,6	16	21	20	10
5511100018	14	3/8	7.5	31	26,5	18	20	21	10
5511100019	14	1/2	9	31	27	18	21	21	10