

55211 TOR-UNIVERSAL-SHORT-CENTRE-LEG

Материал Brass/PVC/1.0619

Налягане PN 20

Размер Ø4,0 - Ø14,0 mm

APPLICATIONS

- Pneumatic automation
- Automotive
- Textile, Packaging
- Compressed Air Circuit
- Vacuum

VARIANTS AND ADVANTAGES

- Quick connection and disconnection
- Full Flow and Vacuum resistant tank to special shaped seals
- 3 threads available:
 - BSPP
 - BSPT (universal short)
 - Metric
- Metal Robustness
- Wide Range
- Silicon Free



No.	Parts	Material
1	Body	Nickel-plated brass
2	Rings	Acetalic resin
3	Capsule	Nickel-plated brass Capsule
4	Clamping washer	Steel AISI 301
5	Position ring	Technopolymeric
6	Molded seal	NBR
7	Thread packing	NBR
8	Threaded base	Nickel Plated Brass
9	Seeger	Seeger
10	Seal	NBR

Specifications	
Standards Reference:	ROHS 2011/65/CE
	PED 2014/68/UE
	ISO 14743:2004
	Sillicon free
Tube diameter:	4,0 - 14,0 mm

Code	Tube	A	B	L1	L2	Ch1	Ch2	D	Bag
------	------	---	---	----	----	-----	-----	---	-----

55211 TOR-UNIVERSAL-SHORT-CENTRE-LEG

Материал Brass/PVC/1.0619

Налягане PN 20

Размер Ø4,0 - Ø14,0 mm

Code	Tube	A	B	L1	L2	Ch1	Ch2	D	Bag
5521100001	4	1/8	5.5	33	18.5	7	13	10	10
5521100002	4	1/4	7	33	20	7	15	10	10
5521100003	5	1/8	5.5	40	20	9	13	12	10
5521100004	6	1/8	5.5	41	20	9	13	12.5	10
5521100005	6	1/4	7	41	21.5	9	15	12.5	10
5521100008	8	1/8	5.5	44	21	10	13	14	10
5521100009	8	1/4	7	44	22.5	10	15	14	10
5521100010	8	3/8	7.5	44	23	10	17	14	10
5521100012	10	1/4	7	53	25.5	13	16	17	10
5521100013	10	3/8	7.5	53	25.5	13	17	17	10
5521100014	10	1/2	9	53	28	13	21	17	10
5521100015	12	1/4	7	60	27	16	16	20	10
5521100016	12	3/8	7.5	60	27	16	17	20	10
5521100017	12	1/2	9	60	29.5	16	21	20	10
5521100018	14	3/8	7.5	61	30	18	20	21	10
5521100019	14	1/2	9	61	30.5	18	21	21	10