

## 55230 TEE CONNECTOR

Материал Brass/PVC/1.0619

Налягане PN 20

Размер Ø4,0 - Ø14,0 mm

### APPLICATIONS

- Pneumatic automation
- Automotive
- Textile, Packaging
- Compressed Air Circuit
- Vacuum

### VARIANTS AND ADVANTAGES

- Quick connection and disconnection
- Full Flow and Vacuum resistant tank to special shaped seals
- 3 threads available:
  - BSPP
  - BSPT (universal short)
  - Metric
- Metal Robustness
- Wide Range
- Silicon Free



No.	Parts	Material
1	Body	Nickel-plated brass
2	Rings	Acetalic resin
3	Capsule	Nickel-plated brass Capsule
4	Clamping washer	Steel AISI 301
5	Position ring	Technopolymeric
6	Molded seal	NBR
7	Thread packing	NBR
8	Threaded base	Nickel Plated Brass
9	Seeger	Seeger
10	Seal	NBR

Specifications	
Standards Reference:	ROHS 2011/65/CE
	PED 2014/68/UE
	ISO 14743:2004
	Sillicon free
Tube diameter:	4,0 - 14,0 mm

Code	Tube	Tube2	Tube3	L1	L2	Ch	D	D1	D2	Bag
------	------	-------	-------	----	----	----	---	----	----	-----

## 55230 TEE CONNECTOR

Материал Brass/PVC/1.0619

Налягане PN 20

Размер Ø4,0 - Ø14,0 mm

Code	Tube	Tube2	Tube3	L1	L2	Ch	D	D1	D2	Bag
5523000002	4	4	4	33	16.5	9	10	4	4	10
5523000019	4	6	4	40	20.5	11	12.5	6	4	10
5523000003	5	5	5	40	20	11	12	5	5	10
5523000004	6	6	6	41	20.5	11	12	6	6	10
5523000009	6	4	6	44	20	11	12.5	4	6	10
5523000005	8	8	8	44	22	13	14	8	8	10
5523000010	8	6	8	45	22.5	13	14	6	8	10
5523000015	8	10	8	52	26.5	16	17	10	8	10
5523000006	10	10	10	53	26.5	16	17	10	10	10
5523000011	10	8	10	53	26	16	17	8	10	10
5523000017	10	12	10	61.5	30	19	20	12	10	10
5523000007	12	12	12	61.5	30	19	20	12	12	10
5523000012	12	10	12	61.5	30	19	20	10	12	10
5523000008	14	14	14	61	30.5	20	21	14	14	10
5523000016	14	8	14	61	30.5	20	21	8	14	10
5523000013	14	10	14	61	30.5	20	21	10	14	10
5523000014	14	12	14	30.5	20	21	61	12	14	10