

55320 CONNECTOR "Y" ORIENTING MALE (UNIVERSAL SHORT)

Материал Brass/PVC/1.0619

Налягане PN 20

Размер Ø4,0 - Ø12,0 mm

APPLICATIONS

- Pneumatic automation
- Automotive
- Textile, Packaging
- Compressed Air Circuit
- Vacuum

VARIANTS AND ADVANTAGES

- Quick connection and disconnection
- Full Flow and Vacuum resistant tank to special shaped seals
- 3 threads available:
 - BSPP
 - BSPT (universal short)
 - Metric
- Metal Robustness
- Wide Range
- Silicon Free



No.	Parts	Material
1	Body	Nickel-plated brass
2	Rings	Acetalic resin
3	Capsule	Nickel-plated brass Capsule
4	Clamping washer	Steel AISI 301
5	Position ring	Technopolymeric
6	Molded seal	NBR
7	Thread packing	NBR
8	Threaded base	Nickel Plated Brass
9	Seeger	Seeger
10	Seal	NBR

Specifications	
Standards Reference:	ROHS 2011/65/CE
	PED 2014/68/UE
	ISO 14743:2004
	Sillicon free
Tube diameter:	4,0 - 12,0 mm

Code	Tube	A	B	C	L	Ch1	Ch2	Bag
------	------	---	---	---	---	-----	-----	-----

55320 CONNECTOR "Y" ORIENTING MALE (UNIVERSAL SHORT)

Материал Brass/PVC/1.0619

Налягане PN 20

Размер Ø4,0 - Ø12,0 mm

Code	Tube	A	B	C	L	Ch1	Ch2	Bag
5532000002	4	1/8	5.5	11	38	10	11	10
5532000007	4	1/4	7	11	40.5	10	14	10
5532000003	6	1/8	5.5	13.5	43	12	11	10
5532000004	6	1/4	7	13.5	45.5	12	14	10
5532000005	8	1/8	5.5	15.5	46.5	14	11	10
5532000006	8	1/4	7	15.5	49	14	14	10
5532000008	8	3/8	7.5	15.5	49.5	14	17	10
5532000009	10	1/4	7	19	56.5	17	14	10
5532000010	10	3/8	7.5	19	57.5	17	17	10
5532000011	10	1/2	9	19	60	17	21	10
5532000012	12	3/8	7.5	22	66,5	20	17	10
5532000013	12	1/2	9	22	68	20	21	10