

55330 MANIFOLD CONNECTOR "Y"

Материал Brass/PVC/1.0619

Налягане PN 20

Размер Ø4,0 - Ø6,0 mm

APPLICATIONS

- Pneumatic automation
- Automotive
- Textile, Packaging
- Compressed Air Circuit
- Vacuum

VARIANTS AND ADVANTAGES

- Quick connection and disconnection
- Full Flow and Vacuum resistant tank to special shaped seals
- 3 threads available:
 - BSPP
 - BSPT (universal short)
 - Metric
- Metal Robustness
- Wide Range
- Silicon Free



No.	Parts	Material
1	Body	Nickel-plated brass
2	Rings	Acetalic resin
3	Capsule	Nickel-plated brass Capsule
4	Clamping washer	Steel AISI 301
5	Position ring	Technopolymeric
6	Molded seal	NBR
7	Thread packing	NBR
8	Threaded base	Nickel Plated Brass
9	Seeger	Seeger
10	Seal	NBR

Specifications	
Standards Reference:	ROHS 2011/65/CE
	PED 2014/68/UE
	ISO 14743:2004
	Sillicon free
Tube diameter:	4,0 - 6,0 mm

55330 MANIFOLD CONNECTOR "Y"

Материал Brass/PVC/1.0619

Налягане PN 20

Размер Ø4,0 - Ø6,0 mm

Code	D1	D2	C	L	F	H	Bag
5533000001	4	4	10.8	33.5	3.3	21.5	10
5533000002	4	6	10.8	34.5	3.3	21.5	10
5533000003	6	6	13.3	39.5	3.3	26.8	10
5533000004	6	8	13.3	40	3.3	26.8	10