

55365 REDUCING MANIFOLD ORIENTING MALE (PARALLEL)

Материал Brass/PVC/1.0619

Налягане PN 20

Размер Ø6,0 - Ø10,0 mm

APPLICATIONS

- Pneumatic automation
- Automotive
- Textile, Packaging
- Compressed Air Circuit
- Vacuum

VARIANTS AND ADVANTAGES

- Quick connection and disconnection
- Full Flow and Vacuum resistant tank to special shaped seals
- 3 threads available:
 - BSPP
 - BSPT (universal short)
 - Metric
- Metal Robustness
- Wide Range
- Silicon Free



No.	Parts	Material
1	Body	Nickel-plated brass
2	Rings	Acetalic resin
3	Capsule	Nickel-plated brass Capsule
4	Clamping washer	Steel AISI 301
5	Position ring	Technopolymeric
6	Molded seal	NBR
7	Thread packing	NBR
8	Threaded base	Nickel Plated Brass
9	Seeger	Seeger
10	Seal	NBR

Specifications	
Standards Reference:	ROHS 2011/65/CE
	PED 2014/68/UE
	ISO 14743:2004
	Sillicon free
Tube diameter:	6,0 - 10,0 mm

Code	Tube	Tube2	F	A	B	L1	L2	C	D1	D2	E	G	Ch	Bag
------	------	-------	---	---	---	----	----	---	----	----	---	---	----	-----

55365 REDUCING MANIFOLD ORIENTING MALE (PARALLEL)

Материал Brass/PVC/1.0619

Налягане PN 20

Размер Ø6,0 - Ø10,0 mm

Code	Tube	Tube2	F	A	B	L1	L2	C	D1	D2	E	G	Ch	Bag
5536500001	6	4	1/8	13.5	6	70.7	21.8	13.5	14	12	3.3	5.4	13	10
5536500002	6	4	1/4	13.5	6	70	21.8	13.5	14	12	3.3	7.1	16	10
5536500003	8	4	1/8	13.5	6	70.7	21.8	13.5	14	12	3.3	5.4	13	10
5536500004	8	4	1/4	13.5	6	70	21.8	13.5	14	12	3.3	7.1	16	10
5536500005	8	6	1/8	13.5	6	70.7	22.3	13.5	14	12.5	3.3	5.4	13	10
5536500006	8	6	1/4	13.5	6	70	22.3	13.5	14	12.5	3.3	7.1	16	10
5536500007	10	6	1/4	15	7	82.4	23.7	15	17	14	3.3	7.1	16	10
5536500008	10	6	3/8	15	7	82	23.7	15	17	14	3.3	8.1	20	10
5536500009	10	8	1/4	15	7	82.4	23.2	15	17	14	3.3	7.1	16	10
5536500010	10	8	3/8	15	7	82	23.2	15	17	14	3.3	8.1	20	10