

55510 STRAIGHT MALE ADAPTOR WITH EXAGON EMBEDDED

Материал Brass/PVC/1.0619

Налягане PN 20

Размер Ø4,0 - Ø8,0 mm

APPLICATIONS

- Pneumatic automation
- Automotive
- Textile, Packaging
- Compressed Air Circuit
- Vacuum

VARIANTS AND ADVANTAGES

- Quick connection and disconnection
- Full Flow and Vacuum resistant tank to special shaped seals
- 3 threads available:
 - BSPP
 - BSPT (universal short)
 - Metric
- Metal Robustness
- Wide Range
- Silicon Free



No.	Parts	Material
1	Body	Nickel-plated brass
2	Rings	Acetalic resin
3	Capsule	Nickel-plated brass Capsule
4	Clamping washer	Steel AISI 301
5	Position ring	Technopolymeric
6	Molded seal	NBR
7	Thread packing	NBR
8	Threaded base	Nickel Plated Brass
9	Seeger	Seeger
10	Seal	NBR

Specifications	
Standards Reference:	ROHS 2011/65/CE
	PED 2014/68/UE
	ISO 14743:2004
	Sillicon free
Tube diameter:	4,0 - 8,0 mm

Code	Tube	A	B	L	Ch	D	Bag
------	------	---	---	---	----	---	-----

55510 STRAIGHT MALE ADAPTOR WITH EXAGON EMBEDDED

Материал Brass/PVC/1.0619

Налягане PN 20

Размер Ø4,0 - Ø8,0 mm

Code	Tube	A	B	L	Ch	D	Bag
5551000001	4	M5	14	39	9	10	10
5551000003	4	1/8	16.5	43	14	10	10
5551000006	5	1/8	16.5	45	14	12	10
5551000007	5	1/4	18.5	50	18	12	10
5551000010	6	1/8	16.5	46	14	12	10
5551000011	6	1/4	18.5	51	18	12	10
5551000012	8	1/8	16.5	47	14	14	10
5551000013	8	1/4	18.5	52	18	14	10