

# 9500 CONNECTOR STRAIGHT FEMALE

Материал brass  
 Налягане PN 20  
 Размер Ø4,0 - Ø18,0 mm

## APPLICATIONS

- Pneumatic Automation
- Automotive
- Textile, Packaging
- Compressed Air Circuit
- Vacuum

## VARIANTS AND ADVANTAGES

- N/A



| No. | Parts             | Material            |
|-----|-------------------|---------------------|
| 1   | Body              | Nickel-plated brass |
| 2   | Compression Rings | Brass               |

| Specifications       |                 |
|----------------------|-----------------|
| Standards Reference: | ROHS 2011/65/CE |
|                      | PED 2014/68/UE  |
|                      | ISO 14743:2004  |
|                      | Silicon free    |
| Tube diameter range: | 4,0 - 18,0 mm   |

| Code      | Tube | A   | B    | L    | Ch | Bag |
|-----------|------|-----|------|------|----|-----|
| 950000001 | 4    | 1/8 | 8.5  | 26.5 | 14 | 10  |
| 950000002 | 6    | 1/8 | 8.5  | 26.5 | 14 | 10  |
| 950000003 | 6    | 1/4 | 11   | 30   | 17 | 10  |
| 950000004 | 8    | 1/8 | 8.5  | 27.5 | 14 | 10  |
| 950000005 | 8    | 1/4 | 11   | 31   | 17 | 10  |
| 950000006 | 8    | 3/8 | 11.5 | 32.5 | 20 | 10  |
| 950000007 | 10   | 1/4 | 11   | 32.5 | 17 | 10  |
| 950000008 | 10   | 3/8 | 11.5 | 34.5 | 20 | 10  |
| 950000009 | 12   | 3/8 | 11.5 | 34.5 | 20 | 10  |

## 9500 CONNECTOR STRAIGHT FEMALE

Материал brass

Налягане PN 20

Размер Ø4,0 - Ø18,0 mm

| Code      | Tube | A   | B  | L    | Ch | Bag |
|-----------|------|-----|----|------|----|-----|
| 950000010 | 12   | 1/2 | 15 | 39   | 24 | 10  |
| 950000011 | 14   | 1/2 | 15 | 40   | 24 | 10  |
| 950000012 | 15   | 1/2 | 15 | 39.5 | 24 | 10  |
| 950000013 | 16   | 1/2 | 15 | 41   | 24 | 10  |
| 950000014 | 18   | 1/2 | 15 | 41   | 26 | 10  |