

BUTTERFLY VALVE STAINLESS STEEL TYPE LUG, DIN PN 10

Материал 1.4408; AISI 316

Налягане PN 10

Размер DN 80 - 600

APPLICATION

High performance, double offset, lug type butterfly valve with one-piece stem. Sealing in PTFE. Top flange according to ISO 5211. Available as variant in cast steel with/without API607.

MEDIA


- Toxic fluids. Corrosive fluids. Fuel oil, lubricating oil and flammable hydraulic oil.
- Non-flammable hydraulic fluid. Boiler feedwater, condensate.
- Seawater and freshwater. Hot water.

VARIANTS

Available in cast steel. With/Without API-607

OPTIONS

Lever, Worm gear, Lever, Electric and pneumatic actuators



No.	Part	Material
1	Body	Stainless steel 1.4401 (AISI316)
2	Disc	Stainless steel 1.4401 (AISI316)
3	Pin	Stainless steel 1.4401 (AISI316)
4	Sealing	PTFE
5	Stem	Stainless steel 1.4401 (AISI316)
6	Packing	PTFE
7	Lever	Ductile iron EN-JS1030 (GGG40)
7	Gear box	Ductile iron EN-JS1030 (GGG40)

Specifications	
Flange Standart:	DIN
Face to face standard:	API 609
Execution:	Straight
Connection type:	Wafer
Operation:	Manual

BUTTERFLY VALVE STAINLESS STEEL TYPE LUG, DIN PN 10

Материал 1.4408; AISI 316

Налягане PN 10

Размер DN 80 - 600

Specifications	
Actuation:	Quarter turn 90°C
Tmax: [°C]	PTFE seat +180°C

Dn	Pressure	L	De	ød	D	ødh	øxn	ød3xøxn	Øh	H	H1	H2	Kg
80	PN 10	48	14	126	76	160	M 16x8	102x12x4 (F10)	16	86	134	140	9
100	PN 10	54	14	155	96	180	M 16x8	102x12x4 (F10)	16	86	144	150	13
150	PN 10	57	17	215	143	240	M 20x8	102x12x4 (F10)	19	89	190	185	19
200	PN 10	62	19	267	188	295	M 20x8	125x14x4 (F12)	21	101	214	215	28
250	PN 10	70	22	326	236	350	M 20x12	125x14x4 (F12)	24	104	254	260	44
300	PN 10	81	27	375	281	400	M 20x12	140x18x4 (F14)	29	129	298	290	66
350	PN 10	92	32	416	320	460	M 20x16	140x18x4 (F14)	34	134	328	320	86
400	PN 10	102	36	480	371	515	M 24x16	165x22x4 (F16)	38	158	377	370	130
450	PN 10	114	36	534	420	565	M 24x20	165x22x4 (F16)	38	158	402	395	163
500	PN 10	127	46	588	469	620	M 24x20	165x22x4 (F16)	48	168	437	430	227
600	PN 10	154	46	692	549	725	M 27x20	254x18x8 (F25)	48	198	492	480	358