

CAST IRON CHECK VALVE DIN PN 16 model 362 Sealing - EPDM / metal

Материал cast iron EN GJL-250; DIN GG25
Налягане PN 16
Размер DN 40 - 300

TECHNICAL DESCRIPTION

Swing check valve with soft disc sealing, flanged connection and bolted cover MODEL 362
Also for installation in vertical pipelines. Upwards flow only.

Min and max Temperature Ts : - 10°C to + 80°C for EPDM seat type Ref.362

WORKING FLUID / MEDIA

Heating, water distribution and watering

OPTIONS

Other materials on request

No.	Part	Material	Specification	
1	Body	Cast iron EN GJL-250 (GG25)	Standart:	DIN 3202 F1
2	Seat ring	Brass	Flange standard:	EN1092-2
3	Disc Ring	EPDM	Face to face standard:	EN558, Series 1
4	Disc	Cast iron EN GJL-250 (GG25)	Bonnet connection:	Bolted
5	Hanger	Ductile iron EN-GJS-400-15	Execution:	Straight
6	Washer	Steel	Connection type:	Flanged
7	Nut	Steel	Operation:	Non-return valve
8	Split pin	AISI 304	Actuation:	Self Return
9	Disc screw	Steel	Tmax	80 °C
10	Hexagon plug	Brass		
11	Hanger pin	AISI 304		
12	Bonnet	Cast iron EN GJL-250 (GG25)		
13	Bonnet gasket	Graphite		
14	Bonnet screw	Steel		
15	Pin	AISI 304		

Dn	Pressure rating	Connection	L	H	øc	ød	øk	Nb x ø l	B	E	Weight (kg)
40	PN 16	PN 16	180	109	84	150	110	4 x 19	18	3	8.5
50	PN 16	PN 16	200	112	99	165	125	4 x 19	20	3	11.2

**CAST IRON CHECK VALVE DIN PN 16 model
362 Sealing - EPDM / metal**

Материал cast iron EN GJL-250; DIN GG25

Налягане PN 16

Размер DN 40 - 300

Dn	Pressure rating	Connection	L	H	øc	ød	øk	Nb x ø l	B	E	Weight (kg)
65	PN 16	PN 16	240	132	118	185	145	4 x 19	20	3	15.5
80	PN 16	PN 16	260	141	132	200	160	8 x 19	22	3	19
100	PN 16	PN 16	300	162	156	220	180	8 x 19	24	3	28.5
125	PN 16	PN 16	350	192	184	250	210	8 x 19	26	3	42.2
150	PN 16	PN 16	400	211	211	285	240	8 x 23	26	3	57
200	PN 16	PN 16	500	270	266	340	295	12 x 23	30	3	93
250	PN 16	PN 16	600	316	319	405	355	12 x 28	32	3	159
300	PN 16	PN 16	700	357	370	460	410	12 x 28	32	4	215