

PRESSURE GAUGE BRASS WITH TEST CONNECTION PN 250

Материал brass / forged
 Налягане PN 250
 Размер G1/2" ; M20x1.5 M/F

APPLICATIONS

Pressure gauge needle valve. Closing valves towards pressure gauge. Tension socket connection M20x1,5

VARIANTS

Metric thread connection: M20x1,5
 Different body materials: Brass / Bronze / Stainless steel



| No. | Part | Material |
|-----|----------------------|------------------------------------|
| 1 | Body | Brass |
| 2 | Primary spindle seal | PTFE |
| 3 | Spindle | Stainless steel 1.4104 / AISI 316L |
| 4 | Operating handwheel | Plastic |
| 5 | Tension socket | Carbon steel 1.0619 |

Specifications

| | |
|--------------------------------|----------------------|
| Standart: | DIN |
| Max. Working Pressure [bar]: | 250 Bar |
| Max. Working Temperature [°C]: | 120 °C |
| Operating: | Manual handwheel |
| Weight: | 0.855 kg |
| Connection 1: | Male thread (BSPP) |
| Connection 1 size: | 1/2" (15) |
| Connection 2: | Female thread (BSPP) |
| Connection 2 size: | 1/2" (15) |
| Tension socket connection: | M20x1,5 |

| Dn | Thread bspp | Pressure range | Weight (kg) |
|----|-------------|----------------|-------------|
| 15 | G1/2" | 0-250,0 Bars | 0,855 |