

55237 ТРОЙНИК ЦЕНТРАЛЕН РАВНОПРОХОДЕН (PLUG-IN)

Материал Brass/PVC/1.0619

Налягане PN 20

Размер Ø6,0 - Ø12,0 mm

APPLICATIONS

- Pneumatic automation
- Automotive
- Textile, Packaging
- Compressed Air Circuit
- Vacuum

VARIANTS AND ADVANTAGES

- Quick connection and disconnection
- Full Flow and Vacuum resistant tank to special shaped seals
- 3 threads available:
 - BSPP
 - BSPT (universal short)
 - Metric
- Metal Robustness
- Wide Range
- Silicon Free



No.	Parts	Material
1	Body	Nickel-plated brass
2	Rings	Acetalic resin
3	Capsule	Nickel-plated brass Capsule
4	Clamping washer	Steel AISI 301
5	Position ring	Technopolymeric
6	Molded seal	NBR
7	Thread packing	NBR
8	Threaded base	Nickel Plated Brass
9	Seeger	Seeger
10	Seal	NBR

Specifications	
Standards Reference:	ROHS 2011/65/CE
	PED 2014/68/UE
	ISO 14743:2004
	Sillicon free
Tube diameter range:	6,0 - 12,0 mm

Code	D1	A	D	B	L	L1	Ch	Bag
------	----	---	---	---	---	----	----	-----

55237 ТРОЙНИК ЦЕНТРАЛЕН РАВНОПРОХОДЕН (PLUG-IN)

Материал Brass/PVC/1.0619

Налягане PN 20

Размер Ø6,0 - Ø12,0 mm

Code	D1	A	D	B	L	L1	Ch	Bag
5523700009	6	4	12.5	15	31.5	41	11	10
5523700010	8	6	14	17	35.5	45	13	10
5523700011	10	8	17	18	40	53	16	10
5523700012	12	10	20	22	47,5	61	19	10